



SPECIFICATIONS

FREQUENCY RANGE: 1.3–2.6 GHz
 ISOALTION: 34dB MIN.
 VSWR: 1.35:1 Max.
 POWER: 10W REV, 50W FWD.
 INSERTION LOSS: 1.0dB MAX.
 OPERATING TEMPERATURE: 0°C to +55°C

MATERIAL:		 MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM	SCALE: N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.02 ±.009 ANGLE: ±1/2°			DRAWING TITLE: DUAL JUNCTION ISOLATOR
DRAWN: Paiboon Luekhamhan DATE: 06-01-2016		PART NO.: ISDJ-11 CAGE CODE: OD2L5 SIZE: N/A REV: N/A DWG NO.: 86621	SHEET: N/A
APPROVED: T. Nguyen DATE: 06-01-2016		THIRD ANGLE PROJECTION 	DO NOT SCALE THE DRAWING