



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

SPECIFICATIONS

Frequency Range: 150–300 MHz
 Insertion Loss: 0.7dB Max.
 Isolation: 19dB Min.
 VSWR: 1.40:1 Max.
 Power: 200 W CW
 Amplitude Balance: ±0.3dB Max.
 Phase Balance: ±5 Deg. Max.

MATERIAL:	
DRAWN: Paiboon Luekhamhan	DATE: 06-08-2011
APPROVED: T. Nguyen	DATE: 06-08-2011

MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC.
 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710
 TEL: (727) 344-6254 FAX: (727) 381-6116
 http://www.MCLI.COM

UNLESS OTHERWISE SPECIFIED:
 TOLERANCES
 IN (INCHES) OR [mm] (MILLIMETERS)
 FRACTIONS: ± 1/64
 DECIMALS: ± .02 ± .009
 ANGLE: ± 1/2°

THIRD ANGLE PROJECTION

SCALE:	N/A
SHEET:	N/A
DRAWING TITLE: 4-WAY POWER DIVIDER/COMBINER	
PART NO.: PM4-6-200/NF	
CAGE CODE: OD2L5	SIZE: N/A
REV: N/A	DWG NO.: 85716
DO NOT SCALE THE DRAWING	