



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

SPECIFICATIONS

Frequency Range: 200–400 MHz
 Insertion Loss: 0.8dB Max.
 Isolation: 19dB Min.
 VSWR: 1.40:1 Max.
 Power: 200 W CW
 Amplitude Balance: ±0.3dB Max.
 Phase Balance: ±5 Deg. Max.

MATERIAL:		 MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://www.mcli.com	SCALE:	N/A
			SHEET:	N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±0.015 ±.007 ANGLE: ±1/2°		DRAWING TITLE: 4-WAY POWER DIVIDER/COMBINER		
DRAWN: Paiboon Luekhamhan		PART NO. PM4-7-200/NF		
DATE: 06-08-2011		CAGE CODE: OD2L5		
APPROVED: T. Nguyen		SIZE: C		REV: N/A
DATE: 06-08-2011		DWG NO. 85717		
THIRD ANGLE PROJECTION		DO NOT SCALE THE DRAWING		