



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

SPECIFICATIONS

Frequency Range: 3.7–4.2 GHz  
 Insertion Loss: 3.9dB Max.  
 Isolation: 19dB Min.  
 Power Handling: 30 Watts Max.  
 VSWR: 1.65:1 Max.  
 Amplitude Balance: ±1.0dB Max.  
 Phase Balance: ±6° Max.

DRAWN: Paboon Luethamhan		DATE: 11-08-1997				<b>MCL</b> MICROPHONE COMMUNICATIONS LABORATORIES INC. 7250 26TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-8254 FAX: (727) 361-8118 <a href="http://www.mcl.com">http://www.mcl.com</a>		SCALE: N/A	
APPROVED: Paboon Luethamhan		DATE: 11-08-1997		UNLESS OTHERWISE SPECIFIED: TOLERANCES: IN (INCHES) OR (mm) MILLIMETERS FRACTIONS ± 1/64 DECIMALS ± 0.01 ± 0.005 ANGLES ± 1/2°		PART NO.: <b>32-WAY POWER DIVIDER</b> <b>PS32-19/NF</b>		SHEET: N/A	
				ORDER CODE: <b>OD2L5</b>		REE: N/A REV: N/A		DWG NO.: <b>80332</b>	
						DO NOT SCALE THE DRAWING			