



ZONE		REV	DESCRIPTION	DATE	APPROVED

SPECIFICATIONS

Frequency Range: 2.2–3.3 GHz
 Waveguide Size: WR340 (Input)
 Flange Types: Per Order (-1,-2,-6,-7)
 VSWR: 1.15 Max.
 Average Power: 5500 Watts

F = FLANGE TYPES

- 1 = CPRG
- 2 = CPRF
- 6 = COVER
- 7 = CHOKE

FLANGE TYPE PER ORDER
 (WR340 CPRF SHOWN)

ORDERING INFORMATION

EXAMPLE PART NUMBER: WL-3-F
 VERY HIGH POWER SERIES
 FREQUENCY BAND
 FLANGE TYPE

Aluminum 6061 High Temp. Black Paint	MCLI MILLER COMMUNICATIONS LABORATORIES 7200 20TH AVE. S. LAKE WASHINGTON, WA 98148 TEL: (206) 844-1000 FAX: (206) 887-0110 WWW: WWW.MCLI.COM	QUANTITY: 1 PART NO.: 5500 WATTS TERMINATION, WR340 REV. NO.: WL-3-F	DATE: N/A REVISION: N/A
DESIGNED: Paloon Luthmanan DATE: 11-09-2013	CHECKED: T. Nguyen DATE: 11-04-2013	DRAWING NO.: OD2L5 PART NO.: WL-3-F	PART NO.: 86409

70x Ø.257 [Ø6.53] THRU

WR340 CPRF STANDRAD
 (UG-1713/U)

DO NOT SCALE THE DRAWING