


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



SPECIFICATIONS

Frequency Range: 225–400 MHz
Coupling: 10 ± 1.0 dB
Frequency Sensitivity: ± 0.75 dB
Insertion Loss: 0.20 dB Max.
Directivity: 22 dB Min.
VSWR: 1.20:1 Max.
Power Incident, Reflected: 20W, 20W, 1kW Peak

MATERIAL:		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A	
		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm .01$ $\pm .008$ ANGLE: $\pm 1/2^\circ$		DRAWING TITLE: DIRECTIONAL COUPLER	
DRAWN: Paiboon Luekhamhan		DATE: 09-10-1998		PART NO. C61-10/TF	
APPROVED: T. Nguyen		DATE: 09-10-1998		CAGE CODE: OD2L5	
		THIRD ANGLE PROJECTION 		SIZE: N/A REV: N/A DWG NO. 86827 DO NOT SCALE THE DRAWING	