


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



**SPECIFICATIONS**

Frequency Range: 0.7–2.7 GHz  
 VSWR: 1.20:1 Max.  
 Coupling: 20±1.0dB  
 Insertion Loss: 0.9dB Max.  
 Directivity: 23dB Min.  
 Frequency Sensitivity: ±0.5dB  
 Power Incident, Reflected, Peak: 50W, 5W, 3kW

MATERIAL:			MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE:	N/A
			UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°		DRAWING TITLE:	DIRECTIONAL COUPLER
DRAWN:		DATE:		PART NO.		DWG NO.
Paiboon Luekhamhan		12-08-2010		CB68-20		
APPROVED:		DATE:		CAGE CODE:	SIZE:	REV:
T. Nguyen		12-08-2010		OD2L5	A	N/A
		PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)		DO NOT SCALE THE DRAWING		85125

