


REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



**SPECIFICATIONS**

- FREQUENCY RANGE: 100-500 MHz
- POWER: 250 Watt CW
- INSERTION LOSS: 0.25dB Max.
- VSWR: 1.25:1 Max.
- FLATNESS: ±0.75dB Max.
- DIRECTIVITY: 20dB Min.

MATERIAL:		<b>MCLI</b> MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 <a href="http://WWW.MCLI.COM">http://WWW.MCLI.COM</a>	SCALE: N/A
			SHEET: N/A
		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°	DRAWING TITLE: <b>30dB DUAL DIRECTIONAL COUPLER</b>
		PROPERTY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)	PART NO.: <b>CL13-30/250</b>
DRAWN: Paiboon luekhamhan	DATE: 09-24-2005	THIRD ANGLE PROJECTION	CAGE CODE: OD2L5
APPROVED: T. Nguyen	DATE: 09-24-2005		SIZE: N/A
			REV: N/A
			DWG NO.: 82413
DO NOT SCALE THE DRAWING			