



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

SPECIFICATIONS

Frequency Range: 800–2000 MHz
 Isolation: 13dB Min.
 Insertion loss: 0.95dB Max.
 VSWR: 1.58:1 Max.
 Power: 50W CW
 Operating Temperature: +10°C to +40°C

MATERIAL:		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7250 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 544-6254 FAX: (727) 381-6110 http://WWW.MCLI.COM	SCALE: N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ± .02 ± .015 ANGLE: ± 1/2°			DRAWING TITLE: COAXIAL CIRCULATOR
DRAWN: Paiboon Luethamhan		DATE: 06-15-2021	PART NO.: CS-139-50
APPROVED: T. Nguyen		DATE: 06-15-2021	CAGE CODE: OD2L5
<small>FOR INFORMATION IN THE DRAWING IS PROPERTY OF MCLI AND WILL BE HELD IN CONFIDENCE UNLESS PERMITTED BY MCLI. COMMUNICATIONS LABORATORIES INC. (MCLI)</small>		SIZE: N/A	REV: N/A
		DO NOT SCALE THE DRAWING	
		DWG NO.: 86907	