


SPECIFICATIONS

Frequency Range: 0.98–2.05 GHz
 Operating Temperature: +10°C to +40°C
 Isolation: 17dB Min.
 Insertion Loss: 0.6dB Max.
 VSWR: 1.35:1 Max.

MATERIAL:		 MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM	SCALE: N/A
			SHEET: N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°		DRAWING TITLE: COAXIAL CIRCULATOR	
DRAWN: Paiboon Luekhamhan		PART NO.: CS-2-1/NMI	
DATE: 11-21-2013		CAGE CODE: OD2L5	
APPROVED: T. Nguyen		DATE: 11-21-2013	
THIRD ANGLE PROJECTION		SIZE: N/A REV: N/A DWG. NO. 86426	
		DO NOT SCALE THE DRAWING	