



REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED

SPECIFICATIONS

Frequency Range: 97.5–102.5 MHz
 Isolation: 20dB Min.
 Insertion loss: 0.50dB Max.
 VSWR: 1.25:1 Max.
 Operating Temperature: 0°C to +55°C
 Peak Power: 100 Watts
 Average Power: 50 Watts

MATERIAL:		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM	SCALE: N/A
			SHEET: N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°		DRAWING TITLE: COAXIAL CIRCULATOR	
DRAWN: Paiboon		PART NO.: CS-331	
DATE: 02-01-2013		CAGE CODE: OD2L5	
APPROVED: Peter Nguyen		DATE: 10-27-2023	
THIRD ANGLE PROJECTION		SIZE: N/A	REV: A
		DWG NO.: 84880	
DO NOT SCALE THE DRAWING			