



REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED

**SPECIFICATIONS**

Frequency Range: 1–2.6 GHz  
 Isolation: 15dB Min.  
 Insertion loss: 0.90dB Max.  
 VSWR: 1.50:1 Max.  
 Operating Temperature: 0°C to +50°C  
 Power: 50W Avg, 100W Peak.

MATERIAL:	
DRAWN: Paiboon Luekhamhan	DATE: 9-05-2007
APPROVED: T. Nguyen	DATE: 09-05-2007



MICROWAVE COMMUNICATIONS LABORATORIES INC.  
 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710  
 TEL: (727) 344-6254 FAX: (727) 381-6116  
 http://WWW.MCLI.COM

SCALE:	N/A
SHEET:	N/A

UNLESS OTHERWISE SPECIFIED:  
 TOLERANCES  
 IN (INCHES) OR [mm] (MILLIMETERS)  
 FRACTIONS: ± 1/64  
 DECIMALS: ±.01 ±.005  
 ANGLE: ±1/2°

DRAWING TITLE:  
**CIRCULATOR**

PART NO.:  
**CS-4**



CAGE CODE:  
**OD2L5**

SIZE: N/A  
 REV: N/A  
 DO NOT SCALE THE DRAWING

DWG NO.:  
**82927**