


REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



SPECIFICATIONS

Frequency Range: 6.4–7.2 GHz
 Isolation: 20dB Min.
 Insertion loss: 0.40dB Max.
 VSWR: 1.25:1 Max.
 Operating Temperature: -54°C to +85°C
 Power Avg: 50 Watts
 Power Peak: 100 Watts
 Hermetically Sealed

MATERIAL:		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM	SCALE:	N/A
			SHEET:	N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°		DRAWING TITLE: COAXIAL CIRCULATOR		
DRAWN: Paiboon Luekhamhan		PART NO. CS-57		
DATE: 07-13-2011		CAGE CODE: OD2L5		
APPROVED: T. Nguyen		DATE: 07-13-2011		SIZE: N/A
THIRD ANGLE PROJECTION		REV: A		DWG NO. 84873
		DO NOT SCALE THE DRAWING		