



REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED

2X M3X5MM, BOTH SIDES



MICROWAVE COMMUNICATIONS LABORATORIES INC.
 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710
 TEL: (727) 344-6254 FAX: (727) 381-6116
 http://WWW.MCLI.COM

SCALE:	N/A
SHEET:	N/A

SPECIFICATIONS
 Frequency Range: 1.3–2.6 GHz
 Isolation: 17dB Min.
 Insertion loss: 0.50dB Max.
 VSWR: 1.35:1 Max.
 Operating Temperature: -10°C to +55°C
 Power: 50W Avg, 100W Peak.

MATERIAL:	
DRAWN:	DATE:
Paiboon Luekhamhan	04-05-2012
APPROVED:	DATE:
T. Nguyen	04-05-2012

UNLESS OTHERWISE SPECIFIED:
 TOLERANCES
 IN (INCHES) OR (mm) (MILLIMETERS)
 FRACTIONS: ± 1/64
 DECIMALS: ±.01 ±.005
 ANGLE: ±1/2°

DRAWING TITLE: COAXIAL CIRCULATOR			
PART NO. CS-6			
CAGE CODE:	SIZE:	REV:	DWG NO.
OD2L5	N/A	A	83863
DO NOT SCALE THE DRAWING			

PROPERTY NOTICE:
 THE INFORMATION IN THIS DRAWING IS PROPRIETARY
 AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN
 PERMISSION FROM MICROWAVE COMMUNICATIONS
 LABORATORIES INC. (MCLI)

THIRD ANGLE PROJECTION