



REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED

**SPECIFICATIONS**

Frequency Range: 0.98–2.50 GHz  
 Isolation: 15dB Min.  
 Insertion loss: 0.9dB Max.  
 VSWR: 1.50:1 Max.

MATERIAL:	
DRAWN: Paiboon Luekhamhan	DATE: 11-22-2013
APPROVED: T. Nguyen	DATE: 11-22-2013

	MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 <a href="http://WWW.MCLI.COM">http://WWW.MCLI.COM</a>		SCALE: N/A
	UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°		SHEET: N/A
DRAWING TITLE: <b>COAXIAL CIRCULATOR</b>		PART NO. <b>CS-73/NMO</b>	
CAGE CODE: <b>OD2L5</b>		SIZE: N/A	REV: N/A
THIRD ANGLE PROJECTION 		DWG NO. <b>86427</b>	
DO NOT SCALE THE DRAWING			