


REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



**SPECIFICATIONS:**

Frequency Range: 2.85–3.30 GHz  
 Isolation: 20dB Min.  
 Insertion loss: 0.35dB Max.  
 VSWR: 1.25:1 Max.

MATERIAL:		<b>MCLI</b> MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE:	N/A
		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°		SHEET:	N/A
DRAWN: Paiboon Luekhamhan		DATE: 05-19-2010	DRAWING TITLE: STRIPLINE INPUT CIRCULATOR		
APPROVED: T. Nguyen		DATE: 05-19-2010	PART NO. CS-78-PI		
THIRD ANGLE PROJECTION		CAGE CODE: OD2L5	SIZE: N/A	REV: N/A	DWG NO. 84839
DO NOT SCALE THE DRAWING					