



REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED

**SPECIFICATIONS**

Frequency Range: 1.5–3 GHz  
 Isolation: 17dB Min.  
 Insertion loss: 0.60dB Max.  
 VSWR: 1.35:1 Max.  
 Operating Temperature: -10°C to +55°C

MATERIAL:		<b>MCLI</b> MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://www.MCLI.COM	SCALE:	N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°			DRAWING TITLE:	COAXIAL CIRCULATOR
DRAWN: Paiboon Luekhamhan		PART NO. CS-7/NF		
DATE: 01-28-2008		CAGE CODE: OD2L5		
APPROVED: T. Nguyen		DATE: 01-28-2008		
PROPRIETARY NOTICE: THE INFORMATION ON THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)		SIZE: A	REV: N/A	DWG NO. 83868
THIRD ANGLE PROJECTION		DO NOT SCALE THE DRAWING		