



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

**SPECIFICATIONS**

Frequency Range: 87–95 MHz  
 Isolation: 20dB Min.  
 Insertion loss: 0.80dB Max.  
 VSWR: 1.20:1 Max.  
 Forward Power: 250W CW  
 Operating Temperature: -10°C to +70°C

MATERIAL		<b>MCLI</b> MICROWAVE COMMUNICATIONS LABORATORIES INC. 7250 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 544-6254 FAX: (727) 381-0110 http://www.mcli.com	SCALE: N/A
DRAWING TITLE: <b>LUMPED ELEMENT COAXIAL CIRCULATOR</b>			SHEET: N/A
PART NO.: <b>CSL-26/NF</b>		DRAWING NO.: <b>86702</b>	
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ± 0.02 ± 0.015 ANGLE: ± 1/2°	DATE: 11-16-2017 DRAWN: Paiboon Luekhamhan	DATE: 11-16-2017 APPROVED: T. Nguyen	CAGE CODE: OD2L5 SIZE: N/A REV: N/A DO NOT SCALE THE DRAWING