REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



PORT CONFIGURATION

Input	90° Out	Isolated	0° Out
1	2	3	4

SPECIFICATIONS

Frequency Center:	1500 MHz
Isolation:	18dB Min.
VSWR:	1.50:1 Max.
Insertion Loss:	0.5dB Max.
Amplitude Balance:	±1.0dB Max.
Phase Balance:	±5 Deg. Max.
Operating Temperature:	−55°C to +85°C

MATERIAL:

MCLI

MICROWAVE COMMUNICATIONS LABORATORIES INC.
7255 30TH AVE. N. SAINT PETERSBURG, FL 33710
TEL: (727) 344-6254 FAX: (727) 381-6116
hhtp://WWW.MCLI.COM

SCALE: N/A
SHEET: N/A

UNLESS OTHERWISE SPECIFIED:
TOLERANCES
IN (INCHES) OR [mm] (MILLIMETERS)
FRACTIONS: ± 1/64
DECIMALS: ±.01 ±.005
ANGLE: ±1/2°

DRAWING TITLE: 90° HYBRID 10% BANDWIDTH

PART NO. HL-17/NF

DRAWN: Paiboon Luekhamhan DATE: 11-29-1997

APPROVED: T. Nguyen DATE: 11-29-1997

PROPRIETARY NOTICE:
THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)

THIRD ANGLE PROJECTION

CAGE CODE: 0D2L5

SIZE: A REV: N/A

DO NOT SCALE THE DRAWING

DWG NO. 80681