


REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



SPECIFICATIONS

Frequency Range: 2-5 GHz
 Isolation: 20dB Min.
 Insertion loss: 0.7dB Max.
 VSWR: 1.25:1 Max.
 Operating Temperature: 25±5C°
 Power: 10 Watts

MATERIAL:		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM	SCALE:	N/A
			SHEET:	N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.04 ±.019 ANGLE: ±1/2°		DRAWING TITLE: COAXIAL ISOLATOR		
DRAWN: Paiboon Luekhamhan		PART NO. IS-200		
DATE: 12-03-2015		CAGE CODE: OD2L5		
APPROVED: T. Nguyen		DATE: 12-03-2015		DWG NO. 86596
THIRD ANGLE PROJECTION 		SIZE: A REV: N/A DO NOT SCALE THE DRAWING		