



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

SPECIFICATIONS AT +25±5°C

Frequency Range: 0.55–1.10 GHz

Isolation: 20dB Min.

Insertion loss: 0.5dB Max.

VSWR: 1.25:1 Max.

Forward Power: 10 Watts

Reverse Power: 10 Watts

DRAWING: Puloon Luekhomhan APPROVED: T. Nguyen DATE: 05-02-2018 DATE: 05-02-2018	MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7230 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-8284 FAX: (727) 381-8118 WWW.MCLI.COM	BOLD: N/A SHEET: N/A
		PART NO.: IS-209 CAGE CODE: 0D2L5 SIZE: N/A REV: N/A DRAW NO.: 86724
UNLESS OTHERWISE SPECIFIED: TOLERANCES: IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ± 0.1 ± 0.05 ANGLES: ± 1/2°		DRAWING TITLE: COAXIAL ISOLATOR DO NOT SCALE THE DRAWING