



REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED

SPECIFICATIONS

Frequency Range: 1–2 GHz
 Isolation: 17dB Min.
 Insertion loss: 0.60dB Max.
 VSWR: 1.38:1 Max.
 Power: 10W Fwd, 1W Rev.
 Operating Temperature: +10°C to +40°C

MATERIAL:		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM	SCALE: N/A
			SHEET: N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°		DRAWING TITLE: COAXIAL ISOLATOR	
DRAWN: Paiboon Luekhamhan		PART NO.: IS-3-10	
DATE: 04-09-2009	DATE: 04-09-2009	CAGE CODE: OD2L5	SIZE: N/A
APPROVED: T. Nguyen	DATE: 04-09-2009	REV: N/A	DWG NO.: 84365
<small>THIRD ANGLE PROJECTION</small> 		DO NOT SCALE THE DRAWING	