



REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED

SPECIFICATIONS

Frequency Range: 0.85–2.5 GHz
 Isolation: 12dB Min.
 Insertion loss: 1.0dB Max.
 VSWR: 1.70:1 Max.
 Forward Power: 60W
 Reverse Power: 15W
 Test Power: 60W
 Operating Temperature: +10°C to +40°C

MATERIAL:		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM	SCALE: N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm .01 \pm .005$ ANGLE: $\pm 1/2^\circ$			DRAWING TITLE: COAXIAL ISOLATOR
DRAWN: Paiboon Luekhamhan DATE: 11-14-2017	PROPIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)	PART NO.: IS-41-15	SHEET: N/A
APPROVED: T. Nguyen DATE: 11-14-2017	THIRD ANGLE PROJECTION 	CAGE CODE: OD2L5 SIZE: N/A REV: N/A DWG NO.: 86699	DO NOT SCALE THE DRAWING