

MECHANICAL

CONTACT : BREAK BEFORE MAKE
 ACTUATOR : FAILSAFE
 SWITCHING SPEED : 20 mSEC MAX


ELECTRICAL

ACTUATOR VOLTAGE: 15.0 Vdc
 ACTUATOR CURRENT: 0.100 A MAX @ 15.0 Vdc
 POWER HANDLING: 200W CW @ 1.0 GHz

ENVIRONMENTAL

OPERATING TEMP : -54° C TO +90° C
 SINE VIBRATION : 30 G'S rms
 LIFE : 1,000,000 CYCLES
 RANDOM VIBRATION : 20 G'S rms


REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



SPECIFICATIONS
 Frequency Range: DC-18.0 GHz
 VSWR: 1.50:1 Max.
 Insertion Loss: 0.50dB
 Isolation: 60dB
 Impedance: 50 Ohms

SCHEMATIC

SHOWN IN FAILSAFE POSITION



MATERIAL:		MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM	SCALE:	N/A
			SHEET:	N/A
DRAWN: Paiboon Luekhamhan		DATE: 06-21-2006	DRAWING TITLE: ELECTROMECHANICAL SWITCHES	
APPROVED: T. Nguyen		DATE: 06-21-2006	PART NO. K1-7-F/15VDC	
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°		FREQUENTLY USED: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)	CAGE CODE: OD2L5	SIZE: N/A REV: N/A DWG. NO. 83997
THIRD ANGLE PROJECTION		DO NOT SCALE THE DRAWING		