



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

SPECIFICATIONS

Frequency Range: 25–1500 MHz
 Insertion Loss: 3.6dB Max.
 Isolation: 20dB Min.
 Amplitude Balance: ±0.7dB Max.
 VSWR: 2.20:1 Max.
 Phase Balance: ±11 Deg. Max.

MATERIAL:	DRAWN: Paboon Luethamhan	DATE: 11-06-1997	MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7250 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 544-6254 FAX: (727) 381-8118 http://www.mcli.com	SCALE: N/A
				SHEET: N/A
APPROVED: T. Nguyen	DATE: 11-06-1997	UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ± 0.01 ± 0.005 ANGLE: ± 1/2°	DRAWING TITLE: 12-WAY POWER DIVIDER PART NO.: PL12-5/NF	
				CAGE CODE: OD2L5 DO NOT SCALE THE DRAWING