



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

SPECIFICATIONS

FREQUENCY RANGE: 1-500 MHz
 INSERTION LOSS: 2.0dB Max.
 VSWR: 1.50:1 Max.
 ISOLATION: 20dB Min.
 AMPLITUDE BALANCE: ±0.6dB Max.
 PHASE BALANCE: ±10 Deg. Max.
 INPUT POWER: 1 Watt

MATERIAL:				MICROWAVE COMMUNICATIONS LABORATORIES INC. 7250 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 544-6254 FAX: (727) 381-8118 http://www.mcli.com		SCALE: N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ± .01 ± .007 ANGLE: ± 1/2°		DRAWING TITLE:		16-WAY POWER DIVIDER		SHEET: N/A
PART NO.:		PL16-12/NF		CAGE CODE: OD2L5		SIZE: C
DRAWING:		DATE: 07-25-2018		REV: N/A		DWG NO.:
APPROVED: T. Nguyen		DATE: 07-25-2018		DO NOT SCALE THE DRAWING		86756