



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

**SPECIFICATIONS**

FREQUENCY RANGE: 200–2000 MHz  
 INSERTION LOSS: 8.0dB Max.  
 VSWR: 1.80:1 Max.  
 ISOLATION: 16dB Min.  
 AMPLITUDE BALANCE:  $\pm 0.8$ dB Max.  
 PHASE BALANCE:  $\pm 12$  Deg. Max.  
 INPUT POWER: 1 Watt

MATERIAL:				MICROWAVE COMMUNICATIONS LABORATORIES INC. 7250 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 544-6254 FAX: (727) 381-8118 http://www.mcli.com		SCALE: N/A
DRAWING TITLE:		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm 0.01 \pm 0.007$ ANGLE: $\pm 1/2^\circ$		DRAWING TITLE: 16-WAY POWER DIVIDER PART NO.: PL16-14/NF		SHEET: N/A
DRAWN: Paiboon	DATE: 07-25-2018	THE INFORMATION ON THIS DRAWING IS PROPERTY OF MCLI AND IS TO BE KEPT IN CONFIDENTIAL STATUS FOR THE USE OF MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)		CAGE CODE: OD2L5 SIZE: C REV: N/A DO NOT SCALE THE DRAWING		DWG NO.: 86757
APPROVED: T. Nguyen	DATE: 07-25-2018			CAGE CODE: OD2L5 SIZE: C REV: N/A DO NOT SCALE THE DRAWING		DWG NO.: 86757