



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

SPECIFICATIONS

FREQUENCY RANGE: 1-200 MHz
 INSERTION LOSS: 1.4dB Max.
 VSWR: 1.40:1 Max.
 ISOLATION: 20dB Min.
 AMPLITUDE BALANCE: ±0.5dB Max.
 PHASE BALANCE: ±8 Deg. Max.
 INPUT POWER: 1 Watt Max.

MATERIAL:				MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 544-6254 FAX: (727) 381-6118 http://www.mcli.com		SCALE: N/A
UNLESS OTHERWISE SPECIFIED:		TOLERANCES		DRAWING TITLE:		
IN (INCHES) OR (mm) (MILLIMETERS)		FRACTIONS: ± 1/64		16-WAY POWER DIVIDER		
DECIMALS: ±0.01 ±0.005		ANGLE: ±1/2°		PART NO.:		
DRAWN: Paiboon Luekhamhan		DATE: 07-18-2006		PL16-2-B-75		
APPROVED: T. Nguyen		DATE: 07-18-2006		CAGE CODE: OD2L5		
				SIZE: C		REV: N/A
				DO NOT SCALE THE DRAWING		DWG NO. 82533