


REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



SPECIFICATIONS

Frequency Range: 20–2000 MHz
 Insertion Loss: 2.5dB Max.
 Isolation: 18dB Min.
 VSWR: 1.60:1 Max.
 Amplitude Balance: ±0.5dB Max.
 Phase Balance: ±8 Deg. Max.

MATERIAL:	
DRAWN: Paiboon Luekhamhan	DATE: 10-12-1997
APPROVED: T. Nguyen	DATE: 10-12-1997



MICROWAVE COMMUNICATIONS LABORATORIES INC.
 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710
 TEL: (727) 344-6254 FAX: (727) 381-6116
 http://WWW.MCLI.COM

SCALE:	N/A
SHEET:	N/A

UNLESS OTHERWISE SPECIFIED:
 TOLERANCES
 IN (INCHES) OR [mm] (MILLIMETERS)
 FRACTIONS: ± 1/64
 DECIMALS: ±.01 ±.005
 ANGLE: ±1/2°

DRAWING TITLE:
3-WAY POWER DIVIDER

PART NO.
PL3-10

CAGE CODE: OD2L5	SIZE: A	REV: A	DWG NO. 80142
DO NOT SCALE THE DRAWING			

