



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

**SPECIFICATIONS**

Frequency Range: 50–1000 MHz  
 Isolation: 24dB Min.  
 Insertion Loss: 1.5dB Max.  
 Amplitude Balance: ±0.5dB Max.  
 Phase Balance: ±8 Deg. Max.  
 VSWR: 1.30:1 Max.

MATERIAL:		 <b>MCLI</b> MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM	SCALE:	N/A
			SHEET:	N/A
		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°	DRAWING TITLE: <b>6-WAY POWER DIVIDER</b>	
DRAWN: Paiboon Luekhamhan		DATE: 03/15/2016	PART NO.: <b>PL6-4/NF</b>	
APPROVED: T. Nguyen		DATE: 03/15/2016	CAGE CODE: OD2L5	SIZE: N/A REV: N/A DNG NO.: 86613
		PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)	DO NOT SCALE THE DRAWING	
		 THIRD ANGLE PROJECTION		