REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



SPECIFICATIONS

Frequency Range:	40–200 MHz
Isolation:	20dB Min.
VSWR:	1.40:1 Max.
Insertion Loss:	1.9dB Max.
Amplitude Balance:	±0.2dB Max.
Phase Balance:	±7 Deg. Max.

MATERIAL:

DRAWN: Paiboon Luekhamhan — DATE: 09-04-2001

APPROVED: T. Nguyen — DATE: 09-04-2001

MCLI
MICROWAVE COMMUNICATIONS LABORATORIES INC.
7255 30TH AVE. N. SAINT PETERSBURG, FL 33710
TEL: (727) 344-8254 FAX: (727) 381-6116
http://WWW.MCLI.COM

UNLESS OTHERWISE SPECIFIED:
TOLERANCES
IN (INCHES) OR [mm] (MILLIMETERS)
FRACTIONS: ± 1/64
DECIMALS: ±.01 ±.005
ANGLE: ±1/2°

PROPRIETARY NOTICE:
THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)

THIRD ANGLE PROJECTION

SCALE: N/A
SHEET: N/A

DRAWING TITLE: 8-WAY LUMPED ELEMENT POWER DIVIDER

PART NO.: PL8-31/BNC

CAGE CODE: 0D2L5

SIZE: N/A | REV: N/A

DWG NO.: 83886

DO NOT SCALE THE DRAWING