



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

SPECIFICATIONS

Frequency Range: 1-200 MHz
 Insertion Loss: 1.7dB Max.
 Isolation: 20dB Min.
 VSWR: 1.50:1 Max.
 Amplitude Balance: ±0.6dB Max.
 Phase Balance: ±5 Deg. Max.

MATERIAL:				MICROWAVE COMMUNICATIONS LABORATORIES INC. 7250 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 544-6254 FAX: (727) 381-8118 http://www.mcli.com		SCALE: N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°		DRAWING TITLE:		8-WAY LUMPED ELEMENT POWER DIVIDER		SHEET: N/A
DRAWN: Paboon Luekhamhan		DATE: 11-05-1997		PART NO. PL8-4/NFI		
APPROVED: T. Nguyen		DATE: 11-05-1997		CAGE CODE: OD2L5		SIZE: N/A REV: N/A DWG NO. 80282
DO NOT SCALE THE DRAWING						