



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

SPECIFICATIONS

Frequency Range: 1–200 MHz
 Insertion Loss: 1.7dB Max.
 Isolation: 20dB Min.
 VSWR: 1.50:1 Max.
 Amplitude Balance: ±0.6dB Max.
 Phase Balance: ±5 Deg. Max.

MATERIAL: 		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 544-6254 FAX: (727) 381-6116 http://www.mcli.com		SCALE: N/A SHEET: N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ± 0.01 ± 0.005 ANGLE: ± 1/2°		DRAWING TITLE: 8-WAY LUMPED ELEMENT POWER DIVIDER		
DRAWN: Pairoon Luekhamhan		DATE: 11-05-1997		PART NO.: PL8-4/NFL
APPROVED: T. Nguyen		DATE: 11-05-1997		CAGE CODE: OD2L5
THE INFORMATION ON THIS DRAWING IS PROPRIETARY AND SHALL NOT BE DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)		SIZE: N/A REV: N/A DO NOT SCALE THE DRAWING	DWG NO.: 80282	