


REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



**SPECIFICATIONS**

Frequency Range: 50–500 MHz  
 Insertion Loss: 1.9dB Max.  
 Isolation: 25dB Min.  
 VSWR: 1.35:1 Max.  
 Amplitude Balance: ±0.5dB Max.  
 Phase Balance: ±4 Deg. Max.  
 Power: 1 Watt Max.

MATERIAL:		<b>MCLI</b> MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 <a href="http://WWW.MCLI.COM">http://WWW.MCLI.COM</a>	SCALE: N/A
			SHEET: N/A
		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°	DRAWING TITLE: <b>8-WAY POWER DIVIDER</b>
		PROPERTY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)	PART NO.: <b>PL8-5</b>
DRAWN: Paiboon Luekhamhan	DATE: 01-06-1997	THIRD ANGLE PROJECTION	CAGE CODE: OD2L5
APPROVED: T. Nguyen	DATE: 01-06-1997		SIZE: N/A
			REV: N/A
			DWG NO.: 80291
DO NOT SCALE THE DRAWING			