



SPECIFICATIONS

Frequency Range: 800–2800 MHz
 Insertion Loss: 0.60dB Min.
 Isolation: 15dB Min.
 Power Rating: 200 W CW
 Amplitude Balance: ± 0.25 dB Max.
 VSWR: 1.35:1 Max.
 Phase Balance: ± 5 Deg. Max.

MATERIAL:		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 544-6254 FAX: (727) 381-8118 http://www.mcli.com		SCALE:	N/A
DRAWING TITLE:				DRAWING TITLE:	4-WAY POWER DIVIDER
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm 0.01 \pm 0.005$ ANGLE: $\pm 1/2^\circ$		PART NO.:		PLH4-13	
DRAWN:	DATE:	CAGE CODE:		SIZE:	REV:
Pai boon Luekhamhan	08-25-2007	OD2L5		N/A	A
APPROVED:	DATE:	DO NOT SCALE THE DRAWING		DWG NO.:	
T. Nguyen	08-25-2007			82949	