



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

**SPECIFICATIONS**

Frequency Range: 100–1000 MHz  
 Insertion Loss: 0.60dB Max.  
 Isolation: 20dB Min.  
 Power: 100 W CW  
 Amplitude Balance: ±0.3dB Max.  
 VSWR: 1.50:1 Max.  
 Phase Balance: ±5 Deg Max.

MATERIAL:		<b>MCLI</b> MICROWAVE COMMUNICATIONS LABORATORIES INC. 7250 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 544-6254 FAX: (727) 381-8110 http://WWW.MCLI.COM	SCALE: N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ± 0.01 ± 0.005 ANGLE: ± 1/2°			SHEET: N/A
DRAWING TITLE: <b>4-WAY POWER DIVIDER</b>		PART NO.: <b>PLH4-2</b>	
DRAWN: <b>Paiboon Luethamhan</b> DATE: <b>02-04-2011</b>	DATE: <b>02-04-2011</b> APPROVED: <b>T. Nguyen</b>	CAGE CODE: <b>OD2L5</b> SIZE: <b>C</b> REV: <b>N/A</b>	DWG NO.: <b>85342</b> DO NOT SCALE THE DRAWING