



SPECIFICATIONS

Frequency Range: 0.01–220 MHz
 Insertion Loss: 1.70dB Max.
 Isolation: 20dB Min.
 Power: 300 W CW
 Amplitude Balance: ± 0.75 dB Max.
 VSWR: 1.35:1 Max.
 Phase Balance: ± 8 Deg Max.

MATERIAL:				MICROWAVE COMMUNICATIONS LABORATORIES INC. 7256 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 544-6254 FAX: (727) 381-6116 http://www.mcli.com		SCALE: N/A
DRAWING TITLE:		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm 0.01 \pm 0.005$ ANGLE: $\pm 1/2^\circ$		4-WAY POWER DIVIDER/COMBINER		SHEET: N/A
PART NO.:		PLH4-20				
DRAWN:	DATE:	THE INFORMATION ON THIS DRAWING IS PROPRIETARY AND SHALL NOT BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT THE WRITTEN PERMISSION OF MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI).		CAGE CODE: OD2L5		DWG NO.:
APPROVED:	DATE:			SIZE: N/A		REV: N/A
				DO NOT SCALE THE DRAWING		85325