



SPECIFICATIONS

Frequency Range: 1.5–30 MHz
 Insertion Loss: 0.25dB Max.
 Isolation: 25dB Min.
 Power: 4,000 W CW
 Amplitude Balance: ± 0.10 dB Max.
 VSWR: 1.20:1 Max.
 Phase Balance: ± 5 Deg Max.

MATERIAL:		 MCLI MICROWAVE COMMUNICATIONS LABORATORIES, INC. 7250 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 544-6254 FAX: (727) 381-0110 http://www.MCLI.COM	SCALE: N/A
DRAWING TITLE:			SHEET: N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm 0.01 \pm 0.005$ ANGLE: $\pm 1/2^\circ$		PART NO. PLH4-27	
DRAWN: Paiboon Luekhamhan	DATE: 02-03-2011	CAGE CODE: OD2L5	
APPROVED: T. Nguyen	DATE: 02-03-2011	SIZE: N/A	REV: N/A
THE INFORMATION ON THIS DRAWING IS PROPRIETARY AND SHALL BE KEPT AS SECRETS UNLESS OTHERWISE PROVIDED FOR SEPARATE COMMUNICATIONS LABORATORIES INC. (MCLI)		DWG NO. 85332	
		DO NOT SCALE THE DRAWING	

14X ϕ .160 [ϕ 4.06] THRU