



SPECIFICATIONS

Frequency Range: 1.5–32 MHz
 Insertion Loss: 0.25dB Max.
 Isolation: 20dB Min.
 Power: 5,000 W CW
 Amplitude Balance: ± 0.15 dB Max.
 VSWR: 1.20:1 Max.
 Phase Balance: ± 5 Deg Max.

MATERIAL:		MCLI MICROWAVE COMMUNICATIONS LABORATORIES, INC. 7256 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 544-6254 FAX: (727) 381-8118 http://www.mcli.com	SCALE: N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm 0.01 \pm 0.005$ ANGLE: $\pm 1/2^\circ$			SHEET: N/A
DRAWING TITLE: 4-WAY POWER COMBINER/DIVIDER		PART NO.: PLH4-28	
DRAWING: Paiboon Luekhamhan	DATE: 02-03-2011	CAGE CODE: OD2L5	SIZE: N/A
APPROVED: T. Nguyen	DATE: 02-03-2011	REV: N/A	DRG NO.: 85332
<small>THE INFORMATION ON THIS DRAWING IS PROPRIETARY AND SHALL NOT BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS WITHOUT THE WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)</small>		<small>DO NOT SCALE THE DRAWING</small>	