



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

4X 6-32 X .25 DP
FAR SIDE ONLY

SPECIFICATIONS

Frequency Range: 3000–3600 MHz
 Insertion Loss: 0.5dB Max.
 Isolation: 15dB Min.
 VSWR: 1.40:1 Max.
 Power: 300 W CW
 Amplitude Balance: ±0.25dB Max.
 Phase Balance: ±5 Deg. Max.

MATERIAL:		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7250 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 544-6254 FAX: (727) 381-0110 http://www.mcli.com	SCALE: N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ± .01 ± .005 ANGLE: ± 1/2°			DRAWING TITLE: 4-WAY POWER DIVIDER/COMBINER
DRAWN: Paiboon Luakhomhan	DATE: 11-22-2011	PART NO. PLH4-37/NF	SHEET: N/A
APPROVED: T. Nguyen	DATE: 11-22-2011	CAGE CODE: OD2L5	SIZE: N/A REV: N/A DWG NO.: 85937
		DO NOT SCALE THE DRAWING	