



SPECIFICATIONS

Frequency Range: 20–1000 MHz
 Insertion Loss: 0.65dB Max.
 Isolation: 15dB Min.
 Power: 1000 Watts CW
 Amplitude Balance: 0.3dB Max.
 VSWR: 1.35:1 Max.
 Phase Balance: ± 5 Deg. Max.

MATERIAL:		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7250 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 544-6254 FAX: (727) 381-0110 http://www.mcli.com		SCALE:	N/A
DRAWING TITLE:				SHEET:	N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: ± 0.015 ANGLE: $\pm 1/2^\circ$		PART NO.		DRAWING TITLE:	
DRAWING: Paiboon Luekhamhan		DATE: 11-08-2012		4-WAY POWER DIVIDER/COMBINER	
APPROVED: T. Nguyen		DATE: 11-08-2012		PART NO. PLH4-39	
CAGE CODE: OD2L5		SIZE: N/A		REV: N/A	
DO NOT SCALE THE DRAWING		DRAW NO. 86190			