REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



SPECIFICATIONS

Frequency Range:	950–1450 MHz
Insertion Loss:	0.6dB Max.
Isolation:	18dB Min.
VSWR:	1.30:1 Max.
Amplitude Balance:	±0.3dB
Phase Balance:	±5 Deg. Max.
Impedance:	75 Ohms

MATERIAL:

MCLI
MICROWAVE COMMUNICATIONS LABORATORIES INC.
7255 30TH AVE. N. SAINT PETERSBURG, FL 33710
TEL: (727) 344-6254 FAX: (727) 381-6116
hhtp://WWW.MCLI.COM

SCALE: N/A
SHEET: N/A

UNLESS OTHERWISE SPECIFIED:
TOLERANCES
IN (INCHES) OR [mm] (MILLIMETERS)
FRACTIONS: ± 1/64
DECIMALS: ±.01 ±.005
ANGLE: ±1/2°

DRAWING TITLE: 2-WAY POWER DIVIDER

PART NO. PM2-40-75/BF

DRAWN:	DATE:
Paiboon Luekhamhan	10-07-1999
APPROVED: T. Nguyen	DATE: 10-07-1999

PROPRIETARY NOTICE:
THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)

THIRD ANGLE PROJECTION

CAGE CODE: 0D2L5

SIZE: A | REV: A

DO NOT SCALE THE DRAWING

DWG NO. 81021