



ZONE		REV	DESCRIPTION	DATE	APPROVED

SPECIFICATIONS

Frequency Range: 300–600 MHz
 Insertion Loss: 1.4dB Max.
 Isolation: 18dB Min.
 VSWR: 1.50:1 Max.
 Power: 200 Watts CW
 Amplitude Balance: ± 0.3 dB Max.
 Phase Balance: ± 5 Deg. Max.

DRAWN:				MICROCOMMUNICATIONS LABORATORIES INC. BOULDER CO. N/A 7250 30TH AVE. N. DAVEN PETERSBURG, FL 32710 TEL: (727) 344-6004 FAX: (727) 361-8118 WWW.MCL.COM	
UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN (INCHES) OR (MILLIMETERS) FINISHES: 1/16" TOLERANCES: ±.015" ANGLE: ±1/2"		8-WAY MICROSTRIP POWER DIVIDER/COMBINER PART NO.		PMB-9-200/NF	
DRAWN: Piboon Luthamhan APPROVED: T. Nguyen	DATE: 08-22-2011 DATE: 08-22-2011	DWG NO.: 85748 SIZE: D REV: N/A	DO NOT SCALE THE DRAWING CHG CODE: OD2LS		