



REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



SPECIFICATION

Frequency Range: 2–18 GHz
 Insertion Loss: 1.0dB Max.
 Isolation: 19dB Min.
 VSWR: 1.40:1 Max.
 Amplitude Balance: ± 0.2 dB Max.
 Phase Balance: ± 5 Deg. Max.
 Power: 30W (Load $v_{swr}@1.2$)

MATERIAL: 		MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A
		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm 0.01 \pm 0.005$ ANGLE: $\pm 1/2^\circ$		SHEET: N/A
DRAWN: Paiboon Luekhamhan DATE: 08-26-2015		DRAWING TITLE: 2-WAY POWER DIVIDER		
APPROVED: T. Nguyen DATE: 08-26-2015		PART NO.: PS2-11-30		
THIRD ANGLE PROJECTION 		CAGE CODE: OD2L5	SIZE: N/A REV: N/A DO NOT SCALE THE DRAWING	DWG NO.: 86587