


REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



SPECIFICATION

Frequency Range: 2–18 GHz
 Insertion Loss: 1.2dB Max.
 Isolation: 19dB Min.
 VSWR: 1.40:1 Max.
 Amplitude Balance: ± 0.3 dB Max.
 Phase Balance: ± 6 Deg. Max.
 Power: 20W (Load vswr@1.2)

MATERIAL: 		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A	
				SHEET: N/A	
DRAWN: Paiboon Luekhamhan DATE: 12-10-1997		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm 0.01 \pm 0.005$ ANGLE: $\pm 1/2^\circ$		DRAWING TITLE: 2-WAY POWER DIVIDER	
				PART NO. PS2-11/S	
APPROVED: T. Nguyen DATE: 12-10-1997		PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)		CAGE CODE: OD2L5	
				SIZE: N/A REV: N/A DWG NO. 80019 DO NOT SCALE THE DRAWING	