


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



**SPECIFICATIONS**

Frequency Range: 10–18.5 GHz  
 Insertion Loss: 2.6dB Max.  
 Isolation: 11dB Min.  
 VSWR In/Out: 2.00:1/1.90:1 Max.  
 Phase Balance: ±12 Deg. Max.  
 Amplitude Balance: 0.6dB Max.  
 Power: 30W (Load vswr@1.2)

MATERIAL:			MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE:	N/A
			UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°		SHEET:	N/A
DRAWING TITLE:		2-WAY POWER DIVIDER				
PART NO.:		PS2-151/NF				
DRAWN:	DATE:	PROPRIETARY NOTICE:	CAGE CODE:	SIZE:	REV:	DWG NO.:
Pai boon Luekhamhan	06-26-1998	THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)	OD2L5	A	A	81211
APPROVED:	DATE:	THIRD ANGLE PROJECTION	DO NOT SCALE THE DRAWING			
T. Nguyen	08-26-1998					