


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



SPECIFICATIONS

Frequency Range: 8–24 GHz
 VSWR In/Out: 1.50:1/1.45:1 Max.
 Insertion Loss: 1.7dB Max.
 Isolation: 19dB Min.
 Amplitude Balance: 0.5dB Max.
 Phase Balance: ±5 Deg. Max.
 Power: 30W (Load vswr@1.2)

MATERIAL:			MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°			DRAWING TITLE: 2-WAY POWER DIVIDER		SHEET: N/A
DRAWN: Paiboon Luekhamhan		DATE: 06-25-1999		PART NO. PS2-162	
APPROVED: T. Nguyen		DATE: 06-25-1999		CAGE CODE: OD2L5	SIZE: A REV: B DWG NO.: 81549 DO NOT SCALE THE DRAWING