



REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED

SPECIFICATIONS

Frequency Range: 250–500 MHz
 Insertion Loss: 0.3dB Max.
 Isolation: 22dB Min.
 VSWR: 1.20:1 Max.
 Amplitude Balance: \pm 0.2dB Max.
 Phase Balance: \pm 2 Deg. Max.
 Power: 30 Watts

MATERIAL:		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM	SCALE:	N/A
			SHEET:	N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: \pm 1/64 DECIMALS: \pm .01 \pm .005 ANGLE: \pm 1/2°		DRAWING TITLE: 2-WAY POWER DIVIDER		
DRAWN: Paiboon Luekhamhan		PART NO.: PS2-176		
DATE: 05-02-2011		CAGE CODE: OD2L5		
APPROVED: T. Nguyen		DATE: 05-02-2011		
THIRD ANGLE PROJECTION		SIZE: N/A		
		REV: B		
		DWG NO.: 85642		
DO NOT SCALE THE DRAWING				