


REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



SPECIFICATIONS

Frequency Range: 0.5–6 GHz
 Insertion Loss: 1.7dB Max.
 Isolation: 19dB Min.
 VSWR In/Out: 1.50:1/1.40:1 Max.
 Phase Balance: ± 10 Deg. Max.
 Amplitude Balance: ± 0.6 dB Max.
 Power: 30W (Load vswr@1.2)

MATERIAL: DRAWN: Paiboon Luekhamhan DATE: 05-06-2009		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A
				SHEET: N/A
APPROVED: T. Nguyen DATE: 05-06-2009		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm 0.01 \pm 0.005$ ANGLE: $\pm 1/2^\circ$ PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI) THIRD ANGLE PROJECTION		DRAWING TITLE: 2-WAY POWER DIVIDER
				PART NO.: PS2-61
		CAGE CODE: OD2L5	SIZE: A DO NOT SCALE THE DRAWING	REV: N/A DWG. NO.: 84436