



REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



SPECIFICATIONS

Frequency Range: 1–28 GHz
Insertion Loss: 2.2dB Max.
Isolation: 16dB Min.
VSWR: 1.60:1 Max.
Amplitude Balance: ± 0.6 dB Max.
Phase Balance: ± 6 Deg. Max.

MATERIAL: 		MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A
		SHEET: N/A		
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm 0.01 \pm 0.005$ ANGLE: $\pm 1/2^\circ$		DRAWING TITLE: 2-WAY POWER DIVIDER		
		PART NO. PS2-79/KF		
DRAWN: Paiboon Luekhamhan	DATE: 12-06-2005	PROPERTY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)	CAGE CODE: OD2L5	
APPROVED: T. Nguyen	DATE: 12-06-2005	THIRD ANGLE PROJECTION 	SIZE: N/A	
		REV: A	DWG NO. 82453	
		DO NOT SCALE THE DRAWING		